

DATA SHEET – CLIO 4BD

| MODELS | TENSION | POWER RATING | CONSUMPTION | AMPERE | FREQUENCY |
|---|---------|--------------|-------------|--------|-----------|
| Heated Display Case AML CLIO LP 4BD, 4 trays | 120V | 505W | 0.505 Kwh | 4.2 A | 50-60 Hz |
| Heated Display Case AML CLIO LC 4BD, 4 trays | 120V | 505W | 0.505 Kwh | 4.2 A | 50-60 Hz |

LC = Led with matte gray / LP = Led with bright black

GENERAL FEATURES:

- > Brushed stainless steel 439/441, 0.5mm thick;
- > Brushed stainless steel 439, 0.5mm thick trays;
- > 4mm and 6mm thick tempered glass;
- > Anodized aluminum frame in matte gray or bright black;
- > Maximum energy consumption of 0.505 Kwh;
- > 500W tubular resistance;
- > Bimetal thermostat (68°F – 248°F)
- > Fiberglass wire 18 AWG max. temp. 842°F;
- > LED light 12V IP20 4.8W/M
- > Electric cable 18AWG American plug NEMA 5-15P;

| SIZE | VOLUME (inner) | NET WEIGHT | PACKAGE | VOLUME (outer) | GROSS WEIGHT |
|-----------------------|----------------|------------|-----------------------|--------------------------|--------------|
| 22.5" x 17.7" x 19.7" | 2400.8 oz | 39.7 lb | 24.6" x 19.5" x 21.7" | 10409.49 in ³ | 44 lb |

